


SIGN DIVA




OLIVE BREEZE
(01-32)



MOONLIGHT SILVER
(01-32)



72 2000-6000 max.



ARTICLE NUMBER 410-8174

500 mA

IP20



50/60Hz

220-240V



MOUNTING

Mounting location: Ceiling
Type: Suspended
Shine ring: Red
Feedcable: T 2000mm / red

ELECTRICAL

Voltage: 220-240V
Control gear needed: Yes
Control gear included: Yes
Dimming: Matter

DIMENSION

Diameter: 400 mm
Height: 72 mm

WEIGHT

Net: 5.35 kg

LIGHT

Adjustability: fixed
Light calculation: Direct
FWHM / Beam Angle: 110°
Diffuser: D Opal

LAMP DESCRIPTION

Lamp type: LED
Total power: 17 W
Power loss ballast: 1.6W
Luminous flux of the light source: 2420 lm
Luminous flux of the luminaire: 1943 lm
Colour rendering index (CRI): 90
MacAdam: 3
LED colour direct: 3000K


ORDER NUMBER

410-8174 30 31 30 01 04 24

TECHNICAL DESCRIPTION

Pendant light (Aluminium); Photometric covers optional: Opal (PMMA), Microprism, Crystal or Industrial; Power feed and canopy (set); Canopy with 2 clamps for further wiring; Ceiling rose and cable pre-assembled; Suspension length 2 or 6m, optionally in the variants transparent, white, black, orange, red.; Individual shortening of the suspension is possible.; 2 powder-coated color options; RAL colors on request; Shine-Ring (optional) optionally in opal, yellow, orange, red, blue or green.; 220-240V Volt, 50/60Hz Hz; "MATTER"- Standard; 3-pole terminal block; Direct light colors: optionally 2700K, 3000K, 3500K or 4000K; CRI > 90; LED board coated with high-reflective material; MacAdam: 3; 80,000 hours lifespan; Flicker-free operation with suitable electronic ballast; directly emitting; Light source can be replaced by professional staff.; complies with EN 60598-1; IP protection type IP20; Electrical Protection Class 1; Height: 72.00 mm; Diameter: 400.00 mm

Polar Curve



Measurement based on the color white



Date: 5/20/2024

We reserve the right to make technical changes without prior notice.

PROLICHT GmbH | Austria | 6091 Götzens | Gewerbepark 9

T +43 5234 33 499 | F +435234 33 499-22 | info@prolicht.at

www.prolicht.at